

TETRA-CHEM INDUSTRIES LTD.



SPECIALTY
CHEMISTRY

INNOVATIVE
ENGINEERING

APPLICATION
TECHNOLOGY

WASTE MANAGEMENT
SERVICES

71 JOHN ST. E., BRIGHT, ON CANADA NOJ 1B0

TEL: (519) 454-4370 (888) 658-5515 FAX: (519) 454-4362
WEB SITE: www.tetra-chem.com EMAIL: info@tetra-chem.com

Check out our Web Site !
www.tetra-chem.com

PRODUCT APPLICATION PRESENTATION

PRODUCT IDENTIFIER:
PROCESS IDENTIFIER:

T C I 5 2 5 H . D .™

**MICRO-ETCH ALUMINUM BRIGHTENER
AND STAINLESS STEEL CLEANER**

PRODUCT PRESENTATION:

TCI 525 H.D. is a blue liquid concentrate of environmentally friendly dilute acids with powerful biodegradable surface active agents. It is designed for the retention and restoration of high optical reflectivity and passivation of stainless steel, as well as brightening of aluminum metal surfaces.

PROCESS INTRODUCTION:

Formula **TCI 525 H.D.** is designed to effectively remove residual dirt, oils, black welding & diesel soot, rust & oxidation on painted surfaces, smut, atmospheric contamination on fiberglass and painted siding, corrosion & oxide films from aluminum and stainless steel surfaces.

PROCESS SPECIFICITY:

TCI 525 H.D. is applied as a light mist to the surface to be cleaned using the Manufacturer's approved Chemical Applicator Manifold System (SEE BROCHURE). This product is designed for cleaning manufactured products such as eg. MOTOR HOMES, RV'S, HORSE TRAILERS, CATTLE POTS, RECYCLING TRUCKS, FEED CARRIERS, SEMI DUMPS, BULK CARRIERS (MILK, FLOUR, CEMENT, PETROLEUM etc.) WHEELS and FUEL TANKS at the maintenance facility of the owner or fleet operators

PRODUCT APPLICATION PROCEDURE:

To start operation, set up the "CHEMICAL APPLICATOR MANIFOLD SYSTEM" and regulate the air pressure to 340-400 kPa (50-60 psi). The pump will operate automatically by starting and stopping the flow on demand at the wand. **CAUTION:** Do not spray TCI 525 H.D. directly onto a hot metal surface since it will alter the chemistry resulting in staining. Walk around the whole unit being treated and thoroughly cool and wet the entire surface on a hot sunny day. The best time is early in the morning or evenings. Spray the chemical solution directly from the drum unto the metal surface and have the PRESSURE WASHER ready for rinsing. Apply the chemical solution as a spray to the entire aluminum surface of the units body starting from the bottom and working up. Assure complete thin film coverage. Once the application is complete, allow approximately a 5 minute chemical exposure time. Exposure time is directly proportional to soil thickness. Brushing is optional.

CAUTION

**DO NOT LET ANY CHEMICAL DRY ON THE SURFACE
(WIND DRIFT CHEMICAL SPRAY IS A POTENTIAL DANGER)**

ie. **CONCENTRATED CHEMICAL WITHOUT WATER MAY STAIN SURFACES IF NOT RINSED**

Rinse the section with high pressure (COLD) water starting at the bottom and consistently moving with a 10 cm fan or less in a horizontal pattern until the top is reached. Then rinse all residual chemical solution thoroughly from the surface working from the top down. When the entire unit is complete, start power washing in the same pattern as the chemical application. If need be re-apply **TCI 525 H.D.** for a second time as a thin film to the entire aluminum surfaces. This will produce an even satin finish. As the new aluminum surface is now exposed to the air it will form a natural aluminum oxide film protecting it against pit corrosion. Accessories on finished products, such as light assemblies, reflectors, plastics, brass, stainless steel, hard chrome, decals, logos, wood, tarps, mud flaps or rubber tires are not altered or defaced by this chemical solution when used according to directions. Glass should be protected from chemical exposure by wetting the surface and immediately rinsing with water. This process does not affect painted surfaces or glass and mirrors as long as the chemical solution does not dry. Unprotected steel surfaces are prone to flash rusting and should be protected with a protective oil or repainted.



Compliments of Westcan
Edmonton, AB



PACKAGING: 04, 25, 205 LITRES

PLEASE CALL OUR TECHNICAL SUPPORT LINE @ 1-888-658-5515 FOR SOLUTIONS TO YOUR INDUSTRY.
CONSULT SERVICE REPRESENTATIVE FOR SAFE AND EFFICIENT APPLICATION

THE INFORMATION GIVEN HEREIN IS GIVEN IN GOOD FAITH BUT NO WARRANTY, EXPRESSED OR IMPLIED IS MADE