

TETRA-CHEM INDUSTRIES LTD.



**SPECIALTY
CHEMISTRY**

**INNOVATIVE
ENGINEERING**

**APPLICATION
TECHNOLOGY**

**WASTE MANAGEMENT
SERVICES**

71 JOHN ST. E., BRIGHT, ON CANADA NOJ 1B0

TEL: (519) 454-4370 (888) 658-5515 FAX: (519) 454-4362
WEB SITE: www.tetra-chem.com EMAIL: info@tetra-chem.com

Check out our Web Site !
www.tetra-chem.com

PRODUCT IDENTIFIER:
PROCESS IDENTIFIER:

PRODUCT APPLICATION PRESENTATION

TCI 700 H.D.TM
TRANSPORTATION CLEANER CONCENTRATE

PRODUCT PRESENTATION

TCI 700 H.D. features a new "HYDROCARBON SOOT AND ROAD FILM SOLVENT" in the form of a super concentrated "GREEN" liquid formulation that combines the cleaning ability of biodegradable detergents, environmentally friendly sequestering agents and mild buffered alkalis. Designed with "PHOSPHATE FREE" chemistry. The water adjustable concentration strength is based on the degree of soil complexity encountered in the transportation industry (TRAINS, TRUCKS & TRAILERS (PAINTED STEEL AND ALUMINUM, VINYL TARPS etc.) UTILITY TRUCKS, AIRCRAFT, SHIPS & BOATS, AGRICULTURAL EQUIPMENT, BUSES, RV'S , CARS AND VANS) at ambient temperatures. Safe on all common surfaces when used according to directions.

PROCESS INTRODUCTION

TCI 700 H.D. is designed for exterior washing when applied with the MANUFACTURER'S approved CHEMICAL APPLICATOR MANIFOLD SYSTEM (SEE BROCHURE) and sprayed as a light mist directly from the mixing tank onto the surface to be cleaned. It may also be applied directly with the siphoning mechanism of a POWER WASHER. The preportioned solution breaks the soil matrix quickly when agitated with a brush and rinsed with warm or cold water pressure at (500-1000 psi). TCI 700 H.D. is ideal for removing heavy encrustation of incomplete combustion by-products from exhaust ports, hydraulic oils, road film, bugs, engine oil and grease. The chemical solution rinses freely and is thus harmless to paint over time. This formulation improves light reflectivity by leaving a rich sheen behind.

PROCESS SPECIFICITY

FUNCTIONALLY MIX TCI 700 H.D. CONCENTRATE AT 2.5-10 % IN WATER DEPENDING ON THE SOIL MATRIX COMPLEXITY. The process can be implemented for the exterior cleaning of all types of painted surfaces, vinyl tarps & awnings, chrome, ferrous and non-ferrous metals (steel and copper), white metals (aluminum and magnesium) where daily or weekly maintenance will not tarnish or dull wheels, fuel tanks, bodies, stainless steel or truck accessories.

PACKAGING:

004, 025, 205 LITRES



TRANSPORTATION INDUSTRY

PLEASE CALL OUR **TECHNICAL SUPPORT LINE @ 1-888-658-5515 FOR SOLUTIONS TO YOUR INDUSTRY.**
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

THE INFORMATION GIVEN HEREIN IS GIVEN IN GOOD FAITH BUT NO WARRANTY, EXPRESSED OR IMPLIED IS MADE